

CARGO CONTROL

Grade 70 Domestic Transport Chain (NACM)



Transport chain is considered the chain of choice for load binding applications. It is also well suited for tie-downs, towing and logging operations. Its strength to weight ratio exceeds that of Proof Coil and High Test. Transport chain meets Department of Transportation regulations. Order unit is foot. **NOT FOR OVERHEAD LIFTING**



Full Drum

Stock #	Trade Size		Wire Dia. (Inches)	Inside Link Dim. (Inches)		Ft. Per Drum	Net Wt. (Lbs.)	Working Load Limit	
	Inches	MM		Length (Nominal)	Width (Nominal)			Lbs.	Kgs.
5041253	1/4	7	0.274	1.235	0.496	800	508	3,150	1,429
5040353*	5/16	8	0.334	1.111	0.505	550	550	4,700	2,132
5041453	3/8	10	0.392	1.370	0.572	400	544	6,600	2,994
5041653	1/2	13	0.509	1.772	0.778	200	460	11,300	5,127
5040853	5/8	16	0.625	1.997	0.882	150	521	15,800	7,166

*Made to Short Link specs

Half Drum

Stock #	Trade Size		Wire Dia. (Inches)	Inside Link Dim. (Inches)		Ft. Per Drum	Net Wt. (Lbs.)	Working Load Limit	
	Inches	MM		Length (Nominal)	Width (Nominal)			Lbs.	Kgs.
5041254	1/4	7	0.274	1.235	0.496	400	254	3,150	1,429
5040354*	5/16	8	0.334	1.111	0.505	275	275	4,700	2,132
5041454	3/8	10	0.392	1.370	0.572	200	272	6,600	2,994
5041654	1/2	13	0.509	1.772	0.778	100	230	11,300	5,127
5040854	5/8	16	0.625	1.997	0.882	75	261	15,800	7,166

*Made to Short Link specs

4 & 5 Gallon Square Pail

Stock #	Trade Size		Wire Dia. (Inches)	Inside Link Dim. (Inches)		Ft. Per Pail	Net Wt. (Lbs.)	Working Load Limit	
	Inches	MM		Length (Nominal)	Width (Nominal)			Lbs.	Kgs.
5340355*	5/16	8	0.334	1.111	0.505	60	62	4,700	2,132
5340455	3/8	10	0.392	1.370	0.572	40	56	6,600	2,994
5440255	1/4	7	0.274	1.235	0.496	150	96	3,150	1,429
5440355*	5/16	8	0.334	1.111	0.505	100	100	4,700	2,132
5440455	3/8	10	0.392	1.370	0.572	75	102	6,600	2,994

*Made to Short Link specs

Box

Stock #	Trade Size		Wire Dia. (Inches)	Inside Link Dim. (Inches)		Ft. Per Box	Net Wt. (Lbs.)	Working Load Limit	
	Inches	MM		Length (Nominal)	Width (Nominal)			Lbs.	Kgs.
5454255	1/4	7	0.274	1.235	0.496	225	148	3,150	1,429
5454355*	5/16	8	0.334	1.111	0.505	150	156	4,700	2,132
5454455	3/8	10	0.392	1.370	0.572	100	140	6,600	2,994

*Made to Short Link specs



All G70 domestic chain (5/16, 3/8, 1/2) is stamped with the Working Load Limit every 10 links as shown.



Find Transport chain accessories on page 53-54.

