

PRODUCT SPECIFICATIONS

# QUIK-SPLICE™



Quik-Splice is a fast-splicing, single braid constructed with high-strength Ultra Blue copolymer olefin fiber. It floats and has high wet and dry abrasion resistance. Sizes 7/16" and smaller change from 12-strand to 8-strand construction.

**FEATURES AND BENEFITS:**

- > 30-35% stronger than standard polypropylene
- > Abrasion resistant, especially in wet environments
- > Easy to splice
- > UV stabilized
- > Water resistant

**APPLICATIONS INCLUDE:**

- > Accessory Product

**PRODUCT CODE:** 335

**FIBER:** Polyolefin

**SPECIFIC GRAVITY:** 0.94

**SPLICE/CLASS:** 12-Strand Class I

**ELASTIC ELONGATION:**

At percent of break strength

10% .....1.10%

20% .....1.90%

30% .....2.60%



DIAM. (INCH)	CIRC. (INCH)	WEIGHT PER 100 FT. (LBS)	AVG. STRENGTH (LBS)	MIN. STRENGTH (LBS)
1/4	3/4	1.1	1,400	1,300
5/16	1	1.7	2,500	2,300
3/8	1 1/8	2.7	3,500	3,200
7/16	1 1/4	3.5	4,600	4,100
1/2	1 1/2	4.9	6,700	6,000
9/16	1 3/4	6	7,500	6,800
5/8	2	8	10,900	9,800
3/4	2 1/4	9.9	13,000	11,700
7/8	2 3/4	15.2	16,000	14,400
1	3	21	23,100	20,800
1 1/8	3 1/2	24.5	28,600	25,700
1 1/4	3 3/4	29	31,300	28,200
1 1/2	4 1/2	41	43,800	39,400
1 5/8	5	51.1	55,000	49,500
1 3/4	5 1/2	60	63,800	57,400
2	6	70	76,300	68,700
2 1/8	6 1/2	84	88,800	79,900
2 1/4	7	98	102,000	91,800
2 1/2	7 1/2	114	113,000	102,000

Specifications are for spliced strengths.